

Megapixel Cube Network Camera

1280 x 800



- Compact and Streamline Design
- Built-in PIR Sensor and Illumination LED
- Built-in MIC and Speaker
- EasyConfig for Easy Set Up and GUI Integration
- Built-in Micro SD Memory Card Slot
- MPEG-4, MJPEG and H.264 Triple Codec Compression
- 802.11b/g/n Wireless Connectivity (WCB-100A)
- WPS Supported for Easy Wireless Network Setup (WCB-100A)

CB-100A Series

The compact Brickcom CB-100A cube network series offers a high quality, video surveillance solution for residences and small businesses. Unlike a general webcam, this camera series is a standalone surveillance system that does not need to be connected to a computer. EasyLink™ is a feature of the CB-100A camera which allows for users to simply plug in the camera to any home or small business network and play the video.

This camera series offers a user-friendly and unique design which allows anyone without a technical background to use it. It features live video feed and two-way audio which can be used over a local area network (LAN), through any internet browser, or via any 3G mobile device. The wireless capability makes it easy to mount on any surface. The CB-100A features many cutting edge functions and its fashionable, streamline design make it the perfect additional for any home or office.

Because of its many advanced features, the CB-100A has many versatile applications. Users can easily monitor the safety of their family members, pets, office, valuables, and property.

Pet Monitor:



The motion detection feature can be used to create forbidden areas in the home which the pet should not enter when the owner is away. If the camera records the pet entering the region, a recorded message can be programmed to play and the owner will be notified via email or MMS.

Residence Monitor:



Home owners worry about their house and property when they are away. The CB-100A has a built-in PIR sensor which can detect unauthorized movement in a residence. Once movement is detected, the illumination LED will be triggered and an alert with a snapshot can be emailed or sent through an MMS to the user's portable device.

Elderly and Child Care:



A high concern for many people is the safety of elderly relatives and small children. Users can use the CB-100A camera to ensure the safety of their loved ones by use of the live view and intercom functions.

Small Office Surveillance:



Security systems for small offices can be expensive and difficult to install and maintain. With the EasyConfig software, the CB-100A can easily be installed and configured by anyone without extensive technical knowledge. The video can be reviewed remotely so business owners can monitor office safety and employee productivity at all times.

CB-100A Series

Product Name

Megapixel Cube Network Camera

Model Number

CB-100A - Ethernet, 2-way audio, PIR, Illumination LED

WCB-100A - Ethernet or WiFi, 2-way audio, PIR, Illumination LED

Hardware System

CPU: 500 MHz

Flash: 16M

RAM: 64M DDR

Image Sensor

Sensor Type : 1/4" Mega-Pixel CMOS Sensor

Sensor Resolution : 1280 x 800 pixel

Minimum Illumination

0 Lux (with LED), 1 Lux (without LED)

Lens

Lens Type : Board Lens

Focal Length: f= 3.74 mm

View Angle : H: 54.8°

V: 35.9°

F-number: F2.0

Video

Auto Exposure Control / Auto White Balance /

Auto Gain Control

Image Compression :

H.264 / MPEG4 / MJPEG

Max Image Resolution

- 1280 x 800: 30fps

Audio

2-way audio

Built-in MIC / Built-in Speaker

Network

Ethernet : one 10/100Mbps RJ-45

WiFi: 802.11 b/g/n (WCB-100A)

Supported Protocols : TCP/IP, UDP, ICMP, DHCP,

NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba,

PPPoE, UPnP, Bonjour, RTP, RTSP, RTCP

Interface & Buttons

Micro SD card slot

DC Power Connector

Ethernet Cable Connector

Privacy Button

WPS Button

Reset Button

Microphone

PIR sensor/ Speaker/ Illumination LED

LEDs

CB-100A

Power / Connect / Internet / Privacy /

Firmware upgrade

WCB-100A

Power / Connect / Internet / Privacy / WPS

Power

Input : DC12V / 1 A (Power Supply)

Max Power consumption

CB-100A: 4.1 w

WCB-100A: 4.5 w

Environment

Operating Temperature: 0°C ~ 50°C (32°F~122°F)

Operating Humidity: 10% ~ 80%

Dimension

29 (L) X60 (W) X 95 (H) mm

Weight

CB-100A: 88g

WCB-100A: 95g

(excluding stand)

Certification

FCC,CE

Warranty

Limited 2-year warranty

