

# rayLUX 25 IP

## WHITE-LIGHT PRODUCT RANGE

The RAYLUX series of High Performance White-Light LED illuminators provide class leading performance, long life and ultra low maintenance. They incorporate the very latest surface mount LED's to deliver excellent night-time pictures with improved optical output and outstanding reliability.



The RAYLUX 25 IP White-Light illuminator is designed to provide dedicated lighting for network cameras via a PoE (Power over Ethernet) enabled infrastructure. Installation is as simple as plugging in the PoE enabled network cable. With an in-built photocell plus internal 'command and control' electronics the RAYLUX 25 IP is truly 'plug and play'.

Each unit is fitted with a Cool Running™ thermal management system to carefully control LED output and delivers a projected working life of 10 years.

RAYLUX 25 IP is suitable for all internal low light installations up to 25 metres (82ft).



## APPLICATIONS



## POWERFUL

- Distances up to 25m (82ft)
- Latest LED technology
- Integrated PSU with command and control electronics

## FLEXIBLE

- PoE input (or 12-24V)
- Various angles (10°, 30°, 50° or 120°)
- One click easy installation

## RELIABLE

- 10 year life
- Cool Running™ thermal management system
- Vandal resistant

## CONTROLLED

- Automatic operation via photocell
- Even Output Illumination
- Excellent Rendition

rayTEC<sup>®</sup>

[www.rayteccctv.com](http://www.rayteccctv.com)

**PoE ENABLED**

The RAYMAX IP and RAYLUX IP series is designed to provide dedicated lighting for IP cameras via a PoE - (Power over Ethernet) enabled network infrastructure. Installation is as simple as plugging in the Ethernet cable. With an in-built photocell plus internal command and control electronics the light is truly plug and play.

**COOL RUNNING™ Thermal Management System**

Cutting edge materials science techniques have been employed to improve thermal efficiency throughout the unit. Cool Running™ is specifically designed to allow all Raytec LED products to provide exceptionally long life - up to 10 years.

**SMT (Surface Mount Technology)**

The future of lighting is surface mount LED technology. Compared to standard through hole LED's, surface mount LED's are a more robust solution increasing reliability and improving product life. They are also far more efficient at the dissipation of heat allowing the LED's to run at higher power and achieve significantly improved performance.

**VANDAL RESISTANT**

The polycarbonate lens design protects against severe blows from crowbars, baseball bats and can even withstand successive shots from air pistols and rifles (range dependant).

**ENERGY SAVING**


All Raytec illuminators use high efficiency LED's and advanced control methods to deliver extremely low electrical consumption. Raytec illuminators are energy saving and deliver huge savings in running costs compared to traditional bulb illuminators.

**HIGH DEFINITION LIGHTING**

High Definition Lighting allows cameras to provide crystal clear, high signal images during the hours of darkness. The breakthrough in HD lighting is made possible with Raytec's high power LED technology delivering increased power on scene.

**3 YEAR WARRANTY**

All Raytec CCTV / IP illuminators are provided with a 3 year warranty, unmatched anywhere in the CCTV lighting industry. Raytec illuminators provide guaranteed long life!

**TECHNICAL SPECIFICATIONS****ILLUMINATOR**

<i>Max Distance:</i>	up to 25m (82ft)
<i>Angle:</i>	10, 30, 50 or 120 degrees
<i>Optics:</i>	SMT LED's
<i>Consumption:</i>	12W max
<i>Weight:</i>	1.0kg
<i>Environmental:</i>	Indoor Applications
<i>Temp Range:</i>	-30 to +50°C (-58 to 122°F)
<i>Colour:</i>	Silver
<i>White-Light:</i>	850 or 950nm
<i>Dimensions:</i>	75 x 100 x 54mm 3" x 4" x 2" approx

**BRACKETRY**

U Bracket included

**INTEGRATED POWER SUPPLY**

<i>Input:</i>	PoE 24V ac/dc 12V dc
<i>Power over Ethernet (PoE):</i>	IEEE802af Compliant Interface Power classification (class 0)
<i>Output:</i>	12W max (adjustable)
<i>Photocell:</i>	Integrated (adjustable sensitivity)
<i>Power Control:</i>	Full 10-100% adjustment

**PART CODES**

RL25-10-IP  
RL25-30-IP  
RL25-50-IP  
RL25-120-IP

RAYLUX 25, 10°  
RAYLUX 25, 30°  
RAYLUX 25, 50°  
RAYLUX 25, 120°

**DISTANCES**

25m (82ft)  
17m (55ft)  
12m (38ft)  
7m (22ft)



Europe / Middle East: Tel: +44 (0) 1670 528446  
Americas: Tel: +1 281 438 3599

Email: sales@rayteccctv.com  
Email: ussales@rayteccctv.com  
Web: www.rayteccctv.com