





Comparison Chart for GV-Joysticks

Model	GV-Joystick	GV-Joystick V2
		
OS Supported		
32-bit	Windows XP / Vista / 7 / Server 2008	Windows XP / Vista / 7 / 8 / Server 2008
64-bit	Windows 7 / Server 2008 R2	Windows 7 / 8 / Server 2008 R2 / Server 2012
Hardware		
USB 2.0	Connects to PC (Virtual Protocol; Driver Required)	Connects to PC (HID Protocol; Plug and Play)
RJ-45	Connects to GV-Keyboard V1 / V2 / V3	Connects to GV-Keyboard V3
Button	4	6 (Customizable)
Dust Proof	No	Yes
General		
Operating Temperature	0 ~ 50°C / 32 ~122°F	
Humidity	5%~95% (non-condensing)	
Power	DC 5V 50mA	
Dimensions (W x H x D)	160 x 90 x 118 mm / 6.30 x 3.54 x 4.65 in	
Weight	310 g / 0.68 lb	500 g / 1.1 lb
Certification	CE, FCC	
Compatible GeoVision Product		
GV-System (DVR/NVR)	Yes	Yes (V8.5.9 or later)
GV-Center V2	Yes	Yes (V8.5.9 or later)
GV-Control Center / GV-Video Wall	Yes	Yes (V3.1.2 or later)
GV-SNVR	No	Yes
GV-IP Decoder Box / GV-Pad	No	Yes (FW V1.06 or later)
GV-IP Decoder Box Plus	No	Yes (FW V1.0 or later)
GV-Keyboard V1	Yes	No
GV-Keyboard V2	Yes	No
GV-Keyboard V3	Yes	Yes (FW V3.0.0.1 or later)

All specifications are subject to change without notice.