

iDS-2CD8447G0/B-RS

DeepinView Triple-Lens Activity Analysis Camera

DeepinView^{series}

Hikvision has been dedicated to develop products with security since established. Hikvision always follows security by design principle and has adopted many methods of security technologies into our product development lifecycle, including terminal security, data security, application security, network security, and privacy protection. In the meantime, the security technologies used by Hikvision are all in compliance with local applicable laws and safety regulations. These security measures could enhance product's cyber security protection capability and protect your devices as well as your data from malicious cyber attacks.

- High quality imaging with 4 MP resolution
- Efficient H.265+ compression technology
- 3D DNR technology delivers clean and sharp images
- Detects up to 10 abnormal events, such as loitering and people falling down
- Adopts high-performance GPU, advanced binocular stereo imaging algorithm and deep learning algorithm
- Supports auto, manual and smart calibration modes
- Filters targets whose height is lower than the threshold and does not perform falling down detection

▪ Specification

Camera	
Image Sensor	Middle lens: 1/1.8" Progressive Scan CMOS, left or right lens: 1/2.7" Progressive Scan CMOS
Min. Illumination	Color: 0.001 Lux @ (F1.2, AGC ON)
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 355°, tilt: 0° to 135°
Lens	
Focal Length & FOV	2.8 mm, horizontal FOV 103°, vertical FOV 51.3°, diagonal FOV 126.1° 4 mm, horizontal FOV 84.2°, vertical FOV 44.4°, diagonal FOV 99.3°
Focus	No
Iris Type	Fixed
Aperture	F1.6
Depth of Field	2.8 mm: 2.1m to ∞ 4 mm: 1.5 m to ∞
DORI	
DORI	2.8 mm: D (Detect): 67.2 m, O (Observe): 26.7 m, R (Recognize): 13.4 m, I (Identify): 6.7 m 4 mm: D (Detect): 76.7 m, O (Observe): 30.4 m, R (Recognize): 15.3 m, I (Identify): 7.7 m
Illuminator	
Supplement Light Type	Speckle light, for analytics only
Supplement Light Range	2.8 mm: Up to 6.6 m, 4 mm: Up to 8.6 m
Supplement Light Number	3
Smart Supplement Light	Yes
IR Wavelength	850 nm
Video	
Main Stream	50 Hz: 25 fps (2560 × 1440, 1920 × 1080, 1280 × 720) 60 Hz: 30 fps (2560 × 1440, 1920 × 1080, 1280 × 720)
Sub-Stream	50 Hz: 25 fps (704 × 576, 640 × 480) 60 Hz: 30 fps (704 × 480, 640 × 480)
Third Stream	50 Hz: 25 fps (1920 × 1080, 1280 × 720, 704 × 576, 640 × 480) 60 Hz: 30 fps (1920 × 1080, 1280 × 720, 704 × 480, 640 × 480)
Fourth Stream	50 Hz: 12.5 fps (1920 × 1080) 60 Hz: 12.5 fps (1920 × 1080)
Video Compression	Main stream: H.265+/H.265/H.264+/ H.264, Sub-stream: H.265/H.264/MJPEG, Third stream: H.265/H.264, Fourth stream: H.265/H.264
Video Bit Rate	32 Kbps to 8 Mbps
H.264 Type	Baseline Profile, Main Profile, High Profile
H.265 Type	Main Profile
Bit Rate Control	CBR, VBR
Scalable Video Coding (SVC)	H.264 and H.265 encoding
Region of Interest (ROI)	Yes

Target Cropping	Yes
Audio	
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM/MP3/AAC-LC
Audio Bit Rate	64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 192 Kbps (MP2L2)/8 to 320 Kbps (MP3)/16 to 64 Kbps (AAC-LC)
Audio Sampling Rate	8 kHz/16 kHz/32 kHz/48 kHz
Environment Noise Filtering	Yes
Image	
Image Parameters Switch	Yes
Image Settings	saturation,brightness,contrast,sharpness,gain,white balance,AGC,adjustable by client software or web browser
Day/Night Switch	Day,Night,Auto,Schedule,Alarm Trigger
Wide Dynamic Range (WDR)	Digital WDR
SNR	≥ 50 dB
Image Enhancement	BLC,3D DNR
Interface	
Ethernet Interface	1 RJ45 10 M/100 M/1000M self-adaptive Ethernet port
On-Board Storage	Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB
Built-in Microphone	Yes, 2 built-in microphones
Built-in Speaker	Yes, 1 built-in speaker
Audio	1 input (line in), two-core terminal block, max. input amplitude: 3.3 Vpp, input impedance: 4.7 KΩ, interface type: non-equilibrium, 1 output (line out), two-core terminal block, max. output amplitude: 3.3 Vpp, output impedance: 100 Ω, interface type: non-equilibrium
Alarm	2 inputs, 2 outputs (max. 24 VDC/24 VAC, 1 A)
RS-485	1 RS-485 (Half duplex, HIKVISION, Pelco-P, Pelco-D, self-adaptive)
Reset Key	Yes
Power Output	12 VDC, max. 100 mA
Indicator	Yes
Event	
Basic Event	Motion detection,video tampering alarm,exception,alarm input and output,video quality diagnosis
Smart Event	scene change detection,audio exception detection,defocus detection
Linkage	Upload to FTP/NAS/memory card,notify surveillance center,send email,trigger alarm output,trigger recording,trigger capture
Deep Learning Function	
Activity Analysis	People Falling Down Detection, Violent Motion Detection, Distance Exception Detection, Person Overstay Detection, People Number Exception Detection, Line Crossing Detection, Loitering Detection, People Running Detection, On-Duty Detection, Intrusion Detection
General	
Power	12 VDC ± 20%, 1 A, max. 13.5 W,two-core terminal block,reverse polarity protection, PoE: IEEE 802.3at, 42.5 V to 57 V, 0.40 A to 0.30 A, Class 4
Material	Metal
Dimension	177.4 mm × 159.3 mm × 126.9 mm (6.98" × 6.27" × 5.0")


Package Dimension	237 mm × 237 mm × 210 mm (9.33" × 9.33" × 8.27")
Weight	Approx. 1280 g (2.82 lb.)
With Package Weight	Approx. 2170 g (4.78 lb.)
Storage Conditions	-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Startup and Operating Conditions	-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Approval	
EMC	CE-EMC: EN 55032:2015+A1:2020, EN 50130-4:2011+A1:2014, EN IEC 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, RCM: AS/NZS CISPR 32: 2015, IC: ICES-003: Issue 7, KC: KN32: 2015, KN35: 2015
Safety	UL: UL 62368-1, CB: IEC 62368-1: 2014+A11, CE-LVD: EN 62368-1: 2014/A11: 2017, BIS: IS 13252 (Part 1): 2010/IEC 60950-1: 2005, LOA: IEC/EN 60950-1
Environment	CE-RoHS: 2011/65/EU, WEEE: 2012/19/EU, Reach: Regulation (EC) No 1907/2006
Transport Certification	IATA Dangerous Goods Regulations, Dangerous Goods List, International Maritime Dangerous Goods Code, Railway Dangerous Goods List

▪ Available Model

iDS-2CD8447G0/B-RS(2.8mm)

iDS-2CD8447G0/B-RS(4mm)

▪ Dimension



Unit: mm

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq