

DS-QAE0MG0G1 Gooseneck Paging Microphone



- High SNR and balanced frequency response sound inlet basket
- Equipped with high sensitivity, low noise pre-amplification circuit, can clearly capture the long-distance speech sound, and provide high quality audio transmission
- With flexible gooseneck design, the angle and direction can be freely adjusted according to needs, and the integrated structure design effectively avoids the problem of product shaking and poor contact caused by multiple insertion and removal of the split structure
- The pickup part adopts the droplet shape design, which can effectively reduce the influence of sound field on the pickup unit
- Using voltage adaptive technology, the product can be compatible with 12 VDC power supply and 48 V phantom power supply
- High quality components and strict test to ensure the reliability of product use
- Support for surveillance center calls



▪ Specification

Microphone	
Type	electret
Pickup Range	0.5 m
Frequency Response	20 Hz to 20 kHz
Sensitivity	-30 dB (0 dB=1 V/Pa@1 kHz)
SNR	70 dB
Dynamic Range	80 dB
Acoustic Overload Point (AOP)	Overload sound 104 dB
Dimension of Sound Inlet Basket	Ø9.7 mm
LEQ	≤24 dB
Adjustment Angel of Gooseneck	360°
Input Current	≤10 mA
Speaker	
Impedance	120 Ω
Interface	
LED Indicator	Key indicator Sound inlet basket indicator
General	
Power	48 V Phantom power,12VDC
Dimension	Base: 35 × 98 × 119 mm (1.38" × 3.86" × 4.69") Gooseneck: 409 mm (16.1")
Weight	Approx. 0.59 kg (1.3 lb.)
Operating Temperature	MAX.35 °C (95 °F)

▪ Available Model

DS-QAE0MG0G1

▪ Dimension



See Far, Go Further



www.hikvision.com
support@hikvision.com

