



Fixed Dome Network Camera FD8151V



1.3MP • Compact Size •
Vandal-proof • Day & Night



VIVOTEK FD8151V is the latest compact fixed dome camera model suitable for a variety of applications. With mounting as easy as one-two-three and Power over Ethernet (PoE) functionality, setup time is completed in less than 120 seconds, making installation quick and easy. The unit is equipped with a vandal-proof housing and IR illuminators up to 5 meters, making it a feature-rich at a competitive price.

The FD8151V features a 1.3-Megapixel sensor enabling viewing resolution of 1280x1024 at 30 fps and also supports the industry-standard H.264 compression technology, drastically reducing file sizes and conserving valuable network bandwidth. With MJPEG compatibility also included, video streams can also be transmitted in either of these formats for versatile applications.

Designed to accept fixed lenses of various focal lengths, FD8151V can be used in various environments, including but not limited to: offices, elevators, campus, chain stores, boutique stores, prisons, and health care facilities. At a size of only 100 mm in diameter, VIVOTEK FD8151V is truly an all-in-one surveillance solution that meets a wide variety of needs for indoor surveillance. The package also includes VIVOTEK's 32-channel recording software. With all this and more, the FD8151V is the ideal solution for your surveillance needs.

Features

- 1.3-Megapixel CMOS Sensor
- Compact Design
- Real-time H.264 and MJPEG Compression (Dual Codec)
- 30 fps @ 1280x1024
- Supreme Night Visibility
- Removable IR-cut Filter for Day and Night Function
- Built-in IR Illuminators, Effective up to 5 Meters
- Built-in IEEE 802.3af Compliant PoE
- Built-in MicroSD/SDHC Card Slot for On-board Storage
- Vandal-proof IK10-rated Housing
- Selectable Lens (f = 2.5 mm or 4 mm)



www.use-ip.co.uk
01304 827609

Technical Specifications

| | | | |
|---------------------------|--|-----------------------------|--|
| Models | FD8151V-F2 (Lens f = 2.5 mm) FD8151V-F4 (Lens f = 4.0 mm) | Network | |
| System Information | | Users | Live viewing for up to 10 clients |
| CPU | Multimedia SoC (System-on-Chip) | Protocols | IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X |
| Flash | 16 MB | Interface | 10Base-T/100 BaseTX Ethernet (RJ-45) |
| RAM | 256 MB | ONVIF | Supported, specification available at www.onvif.org |
| Camera Features | | Intelligent Video | |
| Image Sensor | 1/3" Progressive CMOS | Video Motion Detection | Triple-window video motion detection |
| Maximum Resolution | 1280x1024 | Alarm and Event | |
| Lens Type | Fixed-focal | Alarm Triggers | Video motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification, camera tampering detection |
| Focal Length | f = 2.5 mm (FD8151V-F2) f = 4 mm (FD8151V-F4) | Alarm Events | Event notification using HTTP, SMTP, FTP and NAS server File upload via HTTP, SMTP, FTP and NAS server |
| Aperture | F2.0 (FD8151V-F2) F1.5 (FD8151V-F4) | General | |
| Auto-iris | Fixed-iris | Connectors | RJ-45 for Network/PoE connection Digital input*1 |
| Field of View | FD8151V-F2: 110° (horizontal) 86° (vertical) 142° (diagonal) FD8151V-F4: 64° (horizontal) 53° (vertical) 80° (diagonal) | LED Indicator | System power and status indicator |
| Shutter Time | 1/5 sec. to 1/32,000 sec. | Power Input | IEEE 802.3af PoE Class 2 |
| Day/Night | Removable IR-cut filter for day & night function | Power Consumption | Max. 6.5W |
| Minimum Illumination | FD8151V-F2: 0.16 Lux, 50 IRE (Color) 0.001 Lux, 50 IRE (B/W) FD8151V-F4: 0.1 Lux, 50 IRE (Color) 0.001 Lux, 50 IRE (B/W) | Dimensions | Ø: 100 mm x 55 mm |
| Pan/tilt/zoom | ePTZ: | Weight | Net: 284 g |
| Functionalities | 48x digital zoom (4x on IE plug-in, 12x built-in) | Casing | Vandal-proof IK10-rated metal housing |
| IR Illuminators | Built-in IR illuminators, effective up to 5 meters IR LED*9 | Safety Certifications | CE, LVD, FCC Class B, VCCI, C-Tick |
| On-board Storage | MicroSD/SDHC/SDXC card slot | Operating Temperature | -10°C ~ 50°C (14°F ~ 122°F) |
| Video | | Warranty | 24 months |
| Compression | H.264 & MJPEG | System Requirements | |
| Maximum Frame Rate | H.264: 30 fps at 1280x1024 MJPEG: 30 fps at 1280x1024 | Operating System | Microsoft Windows 7/Vista/XP/2000 |
| Maximum Streams | 2 simultaneous streams | Web Browser | Mozilla Firefox 7~10 (streaming only) Internet Explorer 7.x or 8.x |
| S/N Ratio | Above 58 dB | Other Players | VLC: 1.1.11 or above QuickTime: 7 or above |
| Dynamic Range | 67 dB | Included Accessories | |
| Video Streaming | Adjustable resolution, quality and bitrate Configurable video cropping for bandwidth saving | CD | User's manual, quick installation guide, Installation Wizard 2, ST7501 32-channel recording software |
| Image Settings | Adjustable image size, quality and bit rate Time stamp, text overlay, flip & mirror Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks Scheduled profile settings | Others | Quick installation guide, warranty card, screw pack |
| Audio | | Dimensions | |
| Audio Capability | Audio input | | |
| Compression | G.711 | | |
| Interface | Built-in Microphone | | |

Compatible Accessories

PoE Kits



POE-IJ-1748NDN
PoE injector, 802.3af compliant

All specifications are subject to change without notice. Copyright © 2013 VIVOTEK INC. All rights reserved. P/N: 971007300

Distributed by:



VIVOTEK INC.
6F, No.192, Lien-Cheng Rd., Chung-Ho, New Taipei City, 235, Taiwan, R.O.C.
|T: +886-2-82455282 | F: +886-2-82455532 | E: sales@vivotek.com

VIVOTEK USA, INC.
2050 Ringwood Avenue, San Jose, CA 95131
|T: 408-773-8686 | F: 408-773-8298 | E: salesusa@vivotek.com

Ver 1.1