eyeSpy247

Stop Worrying. Start Seeing.

eyeSpy247 ptz

Key Features

- **Motorised Pan & Tilt with digital Zoom**

- **Night Vision LEDs**

- **One click auto-configuration with Free online services at eyespy247.com**

- **No DDNS, IP address or port forwarding set up needed**

- **VGA resolution (640 x 480) at 30 frames-per-second**

- **MPEG-4 & M-JPEG dual video streaming**

- **Mobile phone 3GPP Live video**

- **802.11g wireless and wired 10/100 Base-T Ethernet**

- **Privacy button**

- **Motion detection & event alerts**

Excellent Price-Performance...

The EyeSpy247PTZ is a high quality, easy-to-use indoor IP Camera. Unlike a Webcam you don't need to connect it to a PC to function or require any special viewing software and is Windows, Mac and Linux friendly.

Despite its compact size, it features motorised pan and tilt, night vision LEDs, two-way audio capability and excellent video quality with VGA resolution at full 30 frames-per-second, MPEG4 and M-JEPG compression, and video latency of just 0.2 second or less.

It supports both wired and wireless connection but unlike most other IP cameras, there's no complicated or fiddly DDNS or other settings to worry about. The unique auto-configuration system built into the camera will help you get it set up for remote viewing from a PC or mobile with just one click!

What's more, the camera has **Exclusive** built-in access to our online platform making it easy to view Live from anywhere plus extensive **Free** services including automated monitoring, video recording, email/SMS intruder alerts, and more.

Now it's easier and more affordable than ever to keep an eye on what's important to you, no matter where you are. Whether it's watching over your home or business, checking when your kids are back from school or looking in on elderly relatives EyeSpy247's complete solution of Internet camera and web based monitoring platform will keep you informed when it matters.

For more information

Web: www.eyespy247.com
Email: info@eyespy247.com
Tel: 0845 5440 288

Video

Image Sensor	CMOS, 1/4" VGA Resolution
Lens	F2.0 Fixed Focus, Effective Range: 50cm to infinity
Compression	MPEG-4 / M-JPEG Dual Stream
Resolution	640 x 480, 320 x 240, 160 x 120
Frame Rate	Up to 30 frame per second in VGA (640 x 480)
Image Control	AWB, AGC, Contrast, Brightness
Video Options	Motion-Detection, Time Stamp, Text Overlay
3GPP	160 x 120 @ 15fs, MPEG-4 for mobile phone viewing

Pan/Tilt/Zoom

Pan Range	320° (Left 160°~Right 160°) + 53° View Angle
Tilt Range	120° (Up 90°~down 30°) + 53° View Angle
Preset Position	10 Preset Positions & Patrol Mode
Digital Zoom	4 x Digital Zoom

Audio

Compression	G.726 ADPCM, G.711 PCM
Mic/Speaker	Bi-directional audio, built-in Mic and external Speaker
Audio Option	On-Off control on web interface

Network

Protocols	TCP / IP, DDNS, SMTP, FTP, HTTP, DHCP, NTP, RTSP / RTP, UPnP

Software

Management	Windows Setup utility, Web based user interface
Client Support	Web Browser, Windows Utility
Security	Username and Password
Users	5 simultaneous users

Wireless

Standard	IEEE 802.11b and 802.11g
Operation Modes	Infrastructure / Ad-Hoc
Range	Indoor: 50m
Encryptions	WEP 64 Bits / 128 Bits, WPA / WPA2 Personal, WPS
Frequency	2.4 ~ 2.4835GHz, DSSS
Antenna	1.8 dbi, Detachable

Hardware

CPU	SC1100 SOC with H/W MPEG- 4/M-JPEG Codec
Flash ROM	4 Megabytes
SDRAM	32 Megabytes
LAN	Ethernet 10/100BaseT
LED Indicators	LED indicator for Power and Network
Connector	Ethernet RJ-45, Speaker, DC Power, Reset
PIR Sensor	Sensitivity distance: 5 meters , Angle: 100°
Night Vision	4 white light LEDs up to 15 feet
Privacy Button	Push button for video enable/disable
Power Adapter	5V/2A, 100/240 VAC
Certification	CE/FCC
Dimensions	(HxWxD)122.18mm x 118.21mm x 107.56mm
Weight	350g (Nett)

Viewing System Requirements

Browsers	Internet Explorer (version 5.5 or later) Firefox, Safari and most other browsers.
Mobiles	Live Images can be viewed via most Internet enabled phones