

## DS-2CD2743G0-IZS 4 MP IR VF Dome Network Camera



### Key Features

- 1/3" Progressive Scan CMOS
- 2560 × 1440@30fps
- 2.8 to 12 mm Varifocal lens
- Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR
- H.265+, H.265, H.264+, H.264
- Three streams
- 120dB WDR
- 2 behavior analyses, and face detection
- BLC/3D DNR/ROI
- IP67, IK10
- Built-in micro SD/SDHC/SDXC card slot, up to 128 GB
- 3-Axis adjustment



## Specifications


| <b>Camera</b>               |   |
|-----------------------------|---|
| Image Sensor                | 1/3" Progressive Scan CMOS  |
| Min. Illumination           | Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR                               |
| Shutter Speed               | 1/3 s to 1/100,000 s  |
| Slow Shutter                | Yes   |
| Auto-Iris                   | No  |
| Day & Night                 | IR Cut Filter   |
| Digital Noise Reduction     | 3D DNR  |
| WDR                         | 120dB   |
| 3-Axis Adjustment           | Pan: 0° to 355°, tilt: 0° to 75°, rotate: 0° to 355°  |
| <b>Lens</b>                 |   |
| Focal length                | 2.8 to 12 mm  |
| Aperture                    | F1.6  |
| Focus                       | Auto  |
| FOV                         | horizontal FOV: 98° to 28°<br>vertical FOV: 51° to 16°<br>diagonal FOV: 115° to 32°                       |
| Lens Mount                  | Φ14   |
| <b>IR</b>                   |   |
| IR Range                    | Up to 30 m  |
| Wavelength                  | 850nm   |
| <b>Compression Standard</b> |   |
| Video Compression           | Main stream: H.265/H.264<br>Sub-stream: H.265/H.264/MJPEG<br>Third stream: H.265/H.264                    |
| H.264 Type                  | Main Profile/High Profile   |
| H.264+                      | Main stream and sub-stream support  |
| H.265 Type                  | Main Profile  |
| H.265+                      | Main stream and sub-stream support  |
| Video Bit Rate              | 32 Kbps to 16 Mbps  |
| Audio Compression           | G.711/G.722.1/G.726/MP2L2/PCM   |
| Audio Bit Rate              | 64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)   |
| <b>Smart Feature-set</b>    |   |
| Behavior Analysis           | Line crossing detection, intrusion detection  |
| Face Detection              | Yes   |
| Region of Interest          | 1 fixed region for main stream and sub-stream   |
| <b>Image</b>                |   |
| Max. Resolution             | 2560 × 1440   |
| Main Stream                 | 50Hz:25fps (2560 × 1440, 2304 × 1296, 1920 × 1080)<br>60Hz: 30fps (2560 × 1440, 2304 × 1296, 1920 × 1080) |
| Sub-Stream                  | 50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)<br>60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)            |
| Third Stream                | 50Hz: 25fps (1280 × 720, 640 × 360, 352 × 288)<br>60Hz: 30fps (1280 × 720, 640 × 360, 352 × 240)          |

|                               |   |
|-------------------------------|---|
| Image Enhancement             | BLC/3D DNR  |
| Image Setting                 | Rotate mode, saturation, brightness, contrast, sharpness adjustable by client software or web browser                             |
| Target Cropping               | No  |
| Day/Night Switch              | Auto/Schedule/Triggered by alarm in   |
| <b>Network</b>                |   |
| Network Storage               | Support Micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR   |
| Alarm Trigger                 | Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD full, HDD error                  |
| Protocols                     | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour |
| General Function              | One-key reset, anti-flicker, three streams, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter    |
| Firmware Version              | V5.5.2  |
| API                           | ONVIF (PROFILE S, PROFILE G), ISAPI   |
| Simultaneous Live View        | Up to 6 channels  |
| User/Host                     | Up to 32 users<br>3 levels: Administrator, Operator and User  |
| Client                        | iVMS-4200, Hik-Connect, iVMS-5200   |
| Web Browser                   | IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+  |
| <b>Interface</b>              |   |
| Audio                         | 1 input (line in/mic.in, 3.5 mm), 1 output (line out, 3.5 mm), mono sound   |
| Communication Interface       | 1 RJ45 10M/100M self-adaptive Ethernet port   |
| Alarm                         | 1 input, 1 output (up to 12 VDC, 30 mA), terminal block   |
| Video Output                  | 1Vp-p Composite Output(75Ω/BNC)   |
| On-board storage              | Built-in Micro SD/SDHC/SDXC slot, up to 128 GB  |
| SVC                           | H.264 and H.265 encoding  |
| Reset Button                  | Yes   |
| <b>Audio</b>                  |   |
| Environment Noise Filtering   | Yes   |
| Audio Sampling Rate           | 16 kHz/32 kHz/44.1 kHz/48 kHz   |
| <b>General</b>                |   |
| Operating Conditions          | -30 °C to +60 °C (-22 °F to +140 °F), Humidity 95% or less (non-condensing)   |
| Power Supply                  | 12 VDC ± 25%, terminal block<br>PoE (802.3af, class 3)  |
| Power Consumption and Current | 12 VDC, 0.8A, max. 10W<br>PoE (802.3af, 37V to 57V), 0.35A to 0.2A, max. 12W  |
| Protection Level              | IP67, IK10<br>TVS 2000V Lightning Protection, Surge Protection and Voltage Transient Protection                                   |
| Material                      | Metal   |
| Dimensions                    | Φ 153.4 × 133.1 mm (Φ 6.0" × 5.2")  |
| Weight                        | Camera: Approx. 1330 g (2.9 lb.)<br>With Package: Approx. 1800 g (4.0 lb.)  |

## Available Model:

DS-2CD2743G0-IZS(2.8 to 12 mm)

**Dimensions**



**Accessories**



DS-1471ZJ-155  
Pendant Mount



DS-1473ZJ-155  
Wall Mount



DS-1475ZJ-SUS  
Vertical Pole Mount



DS-1476ZJ-SUS  
Corner Mount

Distributed by



**HIKVISION**

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Africa**  
T +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision Europe**  
T +31-23-55-42-770  
info.eu@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Oceania**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision Hong Kong**  
T +852-2151-1761

**Hikvision Middle East**  
T +971-4-8816086  
salesme@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Canada**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
potand@hikvision.com

**Hikvision Korea**  
T +82-31-731-8841  
sales.korea@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision UK**  
T +01628-902140  
support.uk@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com