

# AXIS T8343 Alert Button

## Wireless alert button

AXIS T8343 Alert Button is a push button which relays events such as notification messages, illumination, and much more. By communicating wirelessly with AXIS M5065 PTZ Network Camera or connected Z-Wave Plus<sup>®</sup> controllers, the alert button can be used in small security solutions with less cabling. The wireless I/O connectivity also enables flexible installation as the relay can easily be moved and adapted to your needs.

- > **Wireless I/O connectivity**
- > **Z-Wave Plus<sup>®</sup> compatibility**
- > **S2 security compliant**
- > **Battery included**



## AXIS T8343 Alert Button

<b>Supported products</b>	AXIS M5065 PTZ Network Camera Compatible with other Z-Wave Plus® control devices	<b>Approvals</b>	EMC FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, EN 301 489-1 V2.1.1, EN 301 489-13 V2.1.1
<b>Network</b>		<b>Radio</b>	EN 300 220-2 v3.1.1, EN 300 220-2 V3.1.1
<b>Supported protocols</b>	Z-Wave Plus®. For more information on the supported command classes, see the product's User Manual	<b>Safety</b>	EN 62368-1:2014
<b>General</b>		<b>Dimensions</b>	80 x 80 x 18 mm (3.15 x 3.15 x 0.71 in)
<b>Casing</b>	Plastic Color: white	<b>Weight</b>	76 g (0.16 lbs)
<b>Power</b>	2 x AAA 1.5 V Alkaline battery Battery life: 1 year <sup>a</sup>	<b>Included accessories</b>	Installation guide, mounting kit, 2 x AAA 1.5 V Alkaline battery
<b>Distance</b>	Transmitting range up to 100 meters (328 ft)	<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>Frequency</b>	908.42 MHz (US), 922.5 MHz (JP), 868.42 MHz (EU)		
<b>Operating conditions</b>	-10 °C to 40 °C (14 °F to 104 °F)		
<b>Storage conditions</b>	-20 °C to 60 °C (-4 °F to 140 °F)		

a. Measured at 1 trigger per day.

**Environmental responsibility:**  
[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)