

24vAC Inline Power Supplies

Model	HAY- PSUINLINE1A – 24V	HAY- PSUINLINE2A – 24V
Input Range	240 VAC	240 VAC
Input Frequency	50	50
Leakage Current	< 0.5 mA	< 0.5 mA
Rated Output Power	24VA	48VA
Output Voltage	24 VAC±5%	24 VAC±5%
Output Current	1AMP	2AMP
Output Load Efficiency	≥ 70% Min	≥ 70% Min
Adjustment Range	Fixed	Fixed
Insulation Class	B (130°C)	B (130°C)
Protection Class	IP20	IP20
EMC Test	EN55014- 1/-2 EN61000-3-2/-3-3	EN55010- 1/-2 EN61000-3-2/-3-3
Safety Approval	BS EN61558-1/-2-6	BS EN61558-1/-2-6
Operating Temp	- 10°C to 40°C	- 10°C to 40°C
Storage Temp	- 20°C to 70°C	- 20°C to 70°C
Operating Humidity	0% to 90% RH	0% to 90% RH
Size	89.5 x 68 x 58.5mm	105 x 92.5 x 65mm
Cable Length	3.8m	3.8m
UK Plug & 2.1mm Socket	YES	YES

HAY- PSUINLINE1A – 24V



HAY- PSUINLINE2A – 24V

