

AXIS T91B67

Pole Mount for fixed dome cameras

AXIS T91B67 Pole Mount is suitable for all Axis fixed dome cameras compatible with 1.5" NPS threaded Axis pendant kits. Thanks to its impact-resistant and outdoor-proven material, the mount can be used in both indoor and outdoor environments. AXIS T91B67 is intended for poles with a diameter between 65–165 mm (2 1/2–6 1/2 in), and also for beams. It features 3/4" conduit side entries for protected cable runs, and a closed back with cable gasket for protection against insect infestation.

- > **Robust and safe pole installation**
- > **Suitable for indoor and outdoor use**
- > **Impact-resistant to prevent vandalism**
- > **Cable gasket to prevent insect infestation**
- > **Support for 1.5" NPS threaded Axis pendant kits**



AXIS T91B67

General	
Supported products	Axis fixed dome cameras compatible with 1.5" NPS threaded Axis pendant kits
Pole diameter	65–165 mm (2 1/2–6 1/2 in)
Maximum load	15 kg (33 lb)
Cable routing	Back: cable hole Sides: 3/4" Conduit entrance
Casing	NEMA 4X- and IK10-rated powder-coated aluminum mount Color: white NCS S 1002-B Interface: 1.5" NPS
Sustainability	PVC free
Environment	Indoor Outdoor
Approvals	Safety IEC/EN/UL 60950-1, IEC/EN/UL 60950-22 Environment
	IEC 60721, IEC 60721-4 Class 4M3, MIL-STD 810G 509.5, NEMA 250 Type 4X, RoHS, WEEE Impact IEC 62262 IK10
Dimensions	252 x 134 x 194 mm (9.9 x 5.3 x 7.6 in)
Weight	1.2 kg (2.6 lb)
Included accessories	Installation Guide Stainless steel straps Insect-proof cable gasket
Required accessories	1.5" NPS threaded Axis pendant kit
Warranty	Axis 3-year warranty, see www.axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility