

8MP Vandal-Resistant IR Dome Camera

DC-D4831HRX-A



- Easy Installation with DirectIP NVR
- 8MP (3840x2160) Resolution
- Motorized Vari-focal lens (f=2.7 - 13.5mm)
- micro SD / SDHC / SDXC
- Alarm In / Out
- IK10 / IP67
- Built-in heater
- PoE (IEEE 802.3af Class 3), 12V DC
- Day and Night (ICR)
- True Wide Dynamic Range (WDR)
- IR LED (Distance : 40m/131.2ft)
- 3-axis Mechanical Design for Installation
- Supports ONVIF
- NDA Compliance



SPECIFICATIONS

VIDEO	
Image Sensor	1/2.8" CMOS
Max. Resolution	3840 x 2160
Scanning Mode	Progressive Scan
Lens Type	Motorized Vari-focal
Focal Length	f=2.7-13.5mm
Aperture	F1.8 - 3.32
Iris Control	DC IRIS
Angular Field of View	Wide : 110.6°(H) 57.3°(V) 134.1°(D) Tele : 32.6°(H) 18.3°(V) 37.4°(D)
Pan / Tilt Range	Pan: -175° ~ 175°, Tilt: 0° ~ 64°, Rotate: -177° ~ 177°
Min. Illumination	Color : 0.2 Lux @ F1.8 B/W : 0 Lux (IR LED On)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000), Anti-Flicker, Slow Shutter (1~1/5, 1/7.5, 1/15)
Day and Night	IR Cut Filter with Auto Switch
IR Distance (LEDs)	40m / 131.2ft (6ea)
Image Setting	Configurable Exposure, White Balance, Sharpness
Digital Noise Reduction	Configurable 2DNR/3DNR
Backlight Compensation	On / Off
Image Stabilizer	-
De-fog	-
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Video Out	-
NETWORK	
	DirectIP Mode
Video Compression	H.265, H.264 (MP) M-JPEG
Intelligent Codec	Supported
Bitrate Control	H.265 - VBR / CBR H.264 - VBR / CBR
Audio Compression	-
Two-way Audio	-
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S
Max. Frame Rate	30ips : 3840 x 2160 15ips : 3840 x 2160 (WDR)
Supported Resolution	3840 x 2160, 1920 x 1080, 1280 x 720, 640 x 360
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNMP, SMTP, FEN, mDNS, Upnp
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x IP Filtering, HTTPS, SSL Encryption
Remote Access Client	DirectIP NVR Connection, IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)
Edge Storage	micro SD / SDHC / SDXC, Smart Failover (Up to 256GB)
ALARM AND EVENT	
Trigger Event	Motion Detection, Alarm in, Tampering, Trip Zone
Event Notification	Remote S/W, Email (With Image)
Audio In / Out	- / -
Alarm In / Out	1 / 1
ENVIRONMENTAL	
Vandal Proof Casing	IK10
Outdoor Ready	IP67, Heater
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) *Starting Up at Above -20°C (-4°F)
Operating Humidity	0% ~ 90%
ELECTRICAL	
Power Source	PoE (IEEE 802.3af Class 3), DC12V
Power Consumption	12V=, 1.2A, 14.4W PoE, IEEE 802.3af(Class 3), 12.4W
Approvals	FCC, CE, KC
MECHANICAL	
Dimensions	Ø155 x 104.4mm
Weight	1.02 kg(2.25lb)




DIMENSIONS

(Unit - mm)



ACCESSORIES (OPTIONAL)



ACCESSORIES CONFIGURATION TREE

